

Bio Grease M2 HT

Product Data Sheet | Art.no 24.106EP2

Description

Biodegradable, universally applicable grease. Highly water resistant, strong adhesive properties and extremely good anti-corrosion capacity. Suitable for heavy duty bearings, dowels, bushings, chassis points, ball joints, etc.



Available in



400g



18kg



50kg

Typical standard analyses

Colour	Brown
Soap Type	Lithium
Base oil type	Natural ester
Base oil viscosity at 40°C	250
NLGI class	2
Penetration at 60W	265 / 295
Dropping point, °C	Min. 180 °C
Copper corrosion	Max. 1b
Water washout at 80 °C, %	Max. 2,5
Flow pressure at -25 °C	Max. 850 mbar
4-ball wear test, Weld load, kg	Min. 280
4-ball wear test, Wear scar diameter, 1'/80 kg, mm	Max. 0,65 mm
4-ball wear test, wear scar dia, 1h/40 kg	Mac. 0.60 mm
EMCOR Corrosion	0
Oxidation stability 100 °C, kg/cm2	Max. 0,70
Evaporation loss, %, 22 h/100 °C	Max. 0,70
Biodegradability CEC-L-33-A-94	Min. 90
Durability against hydrocarbons	Good

Bio Grease M2 HT

Product Data Sheet | Art.no 24.106EP2

Temperature range, °C

-25 to 120

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE[®]
OIL FOR PROFESSIONALS