

# Food Permisynth 220

Product Data Sheet | Art.no 4Y21.22

## Description

Synthetic gearbox oil, based on PAO constituents. Suitable for gear transmissions that are subjected to heavy and/or shock loads. Can be used in the foodstuffs industry, complies with the USDA-H1 directive.



## Available in



1L



5L



20L

## Typical standard analyses

Density kg/l	0,85
Appearance	Clear
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	218
Viscosity Index	135
Flash Point COC, °C	280
Pour point, °C	-35
Demulsibility, 30 min.	40 - 37-3
Foaming characteristics, 10 min, Sequence I	Nil
Foaming characteristics, 10 min, Sequence II	Nil
Foaming characteristics, 10 min, Sequence III	Nil
Copper corrosion	1b
FZG value	13

## Performance level

InS approved  
NSF approved  
Kosher approved

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)