

# HD Super MO SAE40

Product Data Sheet | Art.no 4A031

## Description

Lubrication oil suitable for petrol engines and also for lighter diesel engines that work under light conditions. Not suitable for turbo-diesel engines for which, minimally, an API CD is prescribed. When correctly applied, suitable as running-in oil for the engine.



## Available in



1L



5L



20L



60L



208L

## Typical standard analyses

Density at 15 °C, kg/l	0,892
Viscosity 40 °C, mm <sup>2</sup> /s	152,00
Viscosity 100 °C, mm <sup>2</sup> /s	15,00
Viscosity Index	97
Flash Point COC, °C	245
Pour Point, °C	-12
Total Base Number, mgKOH/g	3,6
Sulphate Ash, %	0,55

## Performance level

API SF/CC
CCMC G2/D1
Mil-L-46152B/C
Ford M2C153-C (SF/CC)
Ford M2C9011-A
GM 6085M

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: [www.gvg.nl/terms](http://www.gvg.nl/terms)