

Lithium MP EP 2

Product Data Sheet | Art.no 24.101

Description

Universally applicable lubricant. Ensures long-lasting lubrication, is waterproof and adheres well to metal surfaces. Suitable for use at high temperatures. Has high quality Extreme Pressure (EP) properties. Good pumpability at low temperatures and generally suitable for replacing all other lubricants.



Available in



400g



1kg



5kg



18kg



50kg



180kg

Typical standard analyses

Colour	Brown
Soap Type	Lithium
Base oil type	Mineral
NLGI class	2
Unworked penetration at 25 °C	265-295
Dropping point, °C	>180
Welding load	>250 Kg
Oxidation stability 100 °C, bar	<-1.5
EMCOR Corrosion	0
Copper corrosion 24 h / 100 °C	Max 1b
Water washout at 80 °C, %	2.5
Temperature range	-30 up to 120 °C

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms