

Lithium XLD

Product Data Sheet | Art.no 24.139

Description

A very long-lasting grease with excellent adhesion, for a large number of applications in the automotive, agricultural, industrial and building sectors. Is characterised by excellent water resistance and due to its smooth structure is very pumpable.



Available in



390g



18kg



50kg

Application

Suitable for the greasing of heavy duty, slow-rotating or slow-moving bearings, pin & sleeve connectors and other machine components that are subjected to high stress levels. Suitable for use in automatic and/or central lubrication systems.

Typical standard analyses

Soap Type	Lithium
Colour	Yellowish
Dropping point, °C	>180°C
Base oil viscosity at 40°C	680 mm ² /s
Base oil viscosity at 100°C	17 mm ² /s
4-ball weld load	3200 N
4-ball wear test, wear scar dia, 1h/40 kg	0.6 mm
Copper corrosion	1b
Temperature range	-20°C tot 120°C

Instructions for use

Avoid spillages due to excessive grease usage. Seal the packaging properly after use. Do not mix with other types of grease. The safety information sheet for this product is available on request or can be downloaded directly via the website.

Date printed 16-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms