

Truck Line LSP 10W40

Product Data Sheet | Art.no 4A10.15

Description

Modern, fuel saving, low SAPS oil. Developed for heavy duty diesel engines with particulate filter or exhaust gas after treatment systems. Highly suitable for all (off)road uses and contributes to low particle emissions. Offers exceptional resistance against wear and increases the service life of catalytic converters and soot filters.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,864
Viscosity 40 °C, mm ² /s	97,70
Viscosity 100 °C, mm ² /s	14,90
Viscosity Index	160
Flash Point COC, °C	226
Pour Point, °C	-39
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	0,99

Performance level

ACEA E7
ACEA E9
ACEA E11
API-CK-4 / SN
Cat ECF-3
Cummins CES 20086
Detroit Diesel 93K222
Deutz DQC III-18 LA
DTFR 15C100
Ford WSS-M2C171-F1
JASO DH-2
Mack EO-S 4.5
MAN M 3775
MB 228.31
MTU Type 2.1
Renault VI RLD-3
Volvo VDS-4.5

Truck Line LSP 10W40

Product Data Sheet | Art.no 4A10.15

Date printed 27-02-2024

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms

Agealube is een merk van GVG Oliehandel BV.

De Vlotkampweg 77 - 6545 AE Nijmegen NL - T +31 (0)24-675 43 61 - E info@gvg.nl - www.gvg.nl

AGEALUBE[®]
OIL FOR PROFESSIONALS