

Turbosynth LSP Plus 5W30

Product Data Sheet | Art.no 4A10.29

Description

Top quality, low SAPS lubricating oil. Specially developed to save fuel in diesel engines operating under the most difficult conditions in all seasons. Suitable for use with Euro 4, 5 and 6 engines and engines with or without particulate filters and catalytic converters.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,862
Viscosity 40 °C, mm ² /s	72,00
Viscosity 100 °C, mm ² /s	12,10
Viscosity Index	167
Flash Point COC, °C	212
Pour Point, °C	-48
Total Base Number, mgKOH/g	13,4
Sulphate Ash, %	0,96

Performance level

ACEA E4
ACEA E6
ACEA E7
ACEA E8
ACEA E9
ACEA E11
API CK-4
Cat ECF-3
Cummins CES 20086
DAF Extended Drain
Detroit Diesel 93K222
Deutz DQC IV-18 LA
DTFR 15C100
DTRF 15C110
DTFR 15C120
Mack EO-S 4.5
MAN M 3677
MAN M 3691
MAN M 3777
MB 228.31

Turbosynth LSP Plus 5W30

Product Data Sheet | Art.no 4A10.29

MB 228.51

MB 228.52

MTU Type 3.1

Renault VI RLD-3

Scania LDF-4

Volvo VDS-4.5

Date printed 25-03-2024

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms