

Description

Fuel-saving engine oil, suitable for petrol, LPG and diesel engines, with or without turbo, making it possible to prolong intervals between oil changes. Extends the life of the particulate filter thanks to the lows SAPS content.

Application

-

Instructions for use

Check the oil level of your vehicle regularly. Never top up the oil to above the maximum fill indicator line on the dipstick. Use a type of oil as specified in the manual for your vehicle. The safety information sheet is available on request or can be downloaded from the website.

Performance level

ACEA C3-12

API SN

VW 504.00/507.00

BMW Longlife-04

MB 229.31

MB 229.51

MB 229.52

Porsche C30

Typical standard analyses

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	5950
Viscosity 40 °C, mm ² /s	71.60
Viscosity 100 °C, mm ² /s	12.20
Viscosity Index	168
Flash Point COC, °C	234
Pour Point, °C	-39
Total Base Number, mgKOH/g	8.3
Sulphate Ash, %	0,74

Date printed: 19-7-2021

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.