

Description

Engine oil for all petrol and diesel engines of lawn mowers and small machinery. Usable in all seasons. Provides optimal engine protection in the most taxing conditions. Makes for a rapid cold start and is resistant to high temperatures. Keeps engines clean and prevents deposits.

Application

-

Instructions for use

-

Performance level

ACEA A3/B3-10, A3/B4-08

API SL/CF

Typical standard analyses

Density at 15 °C, g/ml	0.875
Kinematic viscosity at 40 °C, mm ² /s	70,4
Kinematic viscosity at 100 °C, mm ² /s	10.9
Viscosity index	145
B.N. (HClO ₄ method), mg KOH/g	7.6
Pour point, °C	-39
CCS viscosity at -25 °C, mPa.s	6750
Sulfated Ash, Mass %	0.85
Flash Point COC, °C	220

Date printed: 3-6-2020

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.