

**Description**

Multifunctional STOU oil for agricultural and earth-moving equipment, specially developed to lubricate petrol and diesel engines, transmissions (also oil-cooled hydraulic brakes) and the hydraulic system.

**Application**

-

**Instructions for use**

-

**Performance level**

API SF/CG-4/GL-4

ACEA E3-96

Mil-L-2104D

Massey Ferguson M1144/M1145

MB 227.1

ZF TE-ML 06B/07B

Ford M2C134-D

Massey Ferguson CMS M1143

John Deere J20C

CAT TO-2

Allison C4

**Typical standard analyses**

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	4850
Viscosity 40 °C, mm <sup>2</sup> /s	88,40
Viscosity 100 °C, mm <sup>2</sup> /s	14,70
Viscosity Index	156
Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,55

Date printed: 3-6-2020

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.