

Description

Fuel-saving, top quality engine oil. Developed for Euro 2 to Euro 6 motors and are specifically prescribed for Scania Euro 6 motors. Suitable for heavy duty diesel engines with or without exhaust gas after treatment systems.

Application

-

Instructions for use

-

Performance level

ACEA E4-12, E7-12

API CF

MAN M 3277

MB-Approval 228.5

Scania LDF-3

Volvo VDS-3

Renault VI RLD-2

Mack EO-N

Renault VI RXD

Typical standard analyses

Density at 15 °C, kg/l	0,869
Viscosity -25 °C, mPa.s	6610
Viscosity 40 °C, mm ² /s	88,30
Viscosity 100 °C, mm ² /s	13,40
Viscosity Index	153
Flash Point COC, °C	220
Pour Point, °C	-36
Total Base Number, mgKOH/g	15,9
Sulphate Ash, %	1,80

Date printed: 3-6-2020

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.