

Description

A lubricating oil suitable for the most intensively used diesel engines, with or without turbo. Specially developed to extend intervals between oil changes. The additives also make it usable with diesel oil with a high sulphur content.

Application

-

Instructions for use

-

Performance level

ACEA E7

API CI-4/SL

MB 228.3

Volvo VDS-3

Renault VI RLD-2

Mack EO-N

Mack EO-M Plus

MAN M 3275-1

Cat ECF-1-a/ECF-2

Cummins CES 20077/20078

Deutz DQC III-10

Detroit Diesel 93K215

Global DHD-1

MTU Type 2

JASO DH-1

Typical standard analyses

Density at 15 °C, kg/l	0,876
Viscosity -20 °C, mPa.s	6500
Viscosity 40 °C, mm ² /s	105,00
Viscosity 100 °C, mm ² /s	13,90
Viscosity Index	133

Date printed: 3-6-2020

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.

Flash Point COC, °C	212
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

Date printed: 3-6-2020

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website.